

Scissor Lift

Used Scissor Lift Fairfield - Scissor lifts are industrial equipment that relies on steel linked arms to lift vertically. This equipment is utilized to create an “X” patterned support in order to accomplish vertical lifting. The scissor lift has a rectangular platform attached to the top of it. To maintain operator safety, there are support railings at the top of the platform. This machine maintains a low profile that is ideal for hard surfaces such as concrete and other compact surfaces. Scissor lifts can use an electric motor or a combustion engine to transport and lift the machine. The lift function operates on a vertical plane only. In order for the operator to transport the lift horizontally, they will have to reposition the lift itself. The same lifting technology is used for the lifting components in regular scissor lift models as well as rough terrain models. The rough terrain is specially designed for traversing uneven ground. Higher ground clearance and oversized all-terrain tires enable these machines to travel to tricky locations. These scissor lifts feature 4WD to get through muddy and difficult terrain. Lower lifting heights are offered due to the higher center of gravity. These machines can be intimidating if you have never been on one or operated one previously. Images of swaying in the wind and being precariously balanced may come to mind. Feel secure knowing you will not feel the lift even moving and you will be in a stable position. Rigorous safety testing has to be completed prior to selling these machines. It is natural to feel unsure of these units until you can familiarize yourself with them. Safety precautions need to be maintained at all times. Depending on the application, there are a variety of electric scissor lift models to pick from. The model you will prefer will largely depend on the types of jobs you plan on completing. Essential factors to consider are the kinds of loads you will be transporting, the weight you will need to lift and how high you will have to go. Extreme heights can be attained by different models depending on your specific application. Tinier models are often preferred for interior jobs such as factory, freight or warehousing situations. If you do not need the highest capacity model, there is no need to choose the largest unit available. There are extra platforms and railings available to provide additional safety measures. These units are safe and reliable. Of course, if these units did not undergo strict inspections and safety certification, they would not be for sale all over the world. These machines help us facilitate tasks that would otherwise not be possible. As these machines vertically elevate, the machine is transported into the correct location before lifting occurs. The operator needs to move the unit into the correct position before engaging the lift. Many safety features have been incorporated into these units. Following operational guidelines is essential for everyone’s safety. Scissor lifts offer a secure basket workspace making many tasks much safer than trying to complete while dangling off of a ladder or scaffolding. The majority of scissor lifts utilize batteries that are internally mounted inside of the base of the lift to generate power. Charging is required after a long sitting for an extended time or working a long shift. Numerous operators charge their units throughout the day or replace batteries every 12 hours. To charge the scissor lift, the operator parks it close to an electrical outlet within a well-ventilated location. When the machine is parked, the emergency shut-off switch becomes engaged to stop. The sizeable red button found inside of the basket or the lift located near the charger or control box is the emergency shut-off switch. The battery charger is commonly located on the right side of the lift on the base. Many older models may feature the battery charger mounted on the back of the scissor lift. The charger for the machine is plugged into the AC extension cord within a well-ventilated area and the extension cord plugs into an electrical outlet. The length of the electrical cord on the battery charger needs to be short to prevent damage or running over it. There is a high possibility for extreme danger if excess extension cord length dropped out of the battery charger storage area during operation. After the scissor lift plugs in to charge, all of the lights should become lit up. Once the unit is plugged in, the batteries automatically start to charge. Once the unit is charged, the battery lights will turn green and the charger will turn off. Older scissor lifts need to use a meter to show zero volts once they are completely charged and this charger also turns off after completion. After the scissor lift is completely

charged, the unit is ready to get back to work. It is common for warehouses and certain businesses to keep batteries charging around the clock to allow the scissor lift to operate 24 hours a day.